


SunLight^{K3}

Technical Specifications



SunLight K3 Single side & Dual side

Memory	2 MB RAM	TECHNOLOGY	Dye-Sublimation Thermal Transfer
Dimensions: H x W x D	SINGLE: 7.9" x 13.62"x8,14"/201x346x207mm DUAL: 7.9"x18,28"x8,14"/201x464x207mm	SPEED K	1 card in monochrome in 7 sec. 514 cards per hour
Weight	SINGLE: 8lbs./3,63kg DUAL: 11.5 lbs./5,22 kg	SPEED YMCKO	1 color card (1 side) in 27 sec. 133 cards per hour
Power Supply	100 - 240 VAC - 50/60 HZ	SPEED YMCKOK Only DUAL version	1 color card (front) and black (back in 35 sec. 102 cards Hr.
Warranty	24 MONTHS	RESOLUTION	300 dpi (11.8 dots/mm)
Operating System	Windows 200/XP/Server 2003	COLORS	Up to 16.7 million / pixel 256 shades per pixel
SW	RAINBOW LIGHT Included RAINBOW SMART available on request	PRINT AREA	CR 80: edge-to-edge
USB	STANDARD	FLIP OVER	Only DUAL version
Ethernet	OPTIONAL	BAR CODE	via Windows driver; 2/5, 2/5 Interleaved, Code 39, Ean 8, Ean 13, managed by the software
ISO Formats	CR 80: 85,6 X 54 MM	Magnetic stripe encoding	ISO Hi-Co e Lo-Co, Tracce 1,2 e 3
Card Thickness	from 0,51 to 0,76 mm 0.02" to 0.03"	CHIP Docking Station*	YES
Card Material	PVC - PVC composite	Smart Card Encoder Contact*	Cards with memory and microprocessor ISO 7816 - 1/2/3/4 (T=0, T=1); Synchronous cards
Input Hopper	100 card (O 0,76 mm / 0.03")	Smart Card Encoder Contact-less*	HID® iCLASS, MIFARE® e MIFARE /DESFire
Output Hopper	30 cards (optional 100)	Prox Card Encoder*	HID - read-only



Warranty Upgrade provides a loaner printer with exact configuration
by 2nd day shipping. 3 Year maximum renewal.
Service Agreement is 4 scheduled service calls per yr. to Clean, Calibrate
& Adjust Printer within our local service area.



Image Sales, Inc.
1559 Third Avenue
Walnut Creek, CA 94597
Phone: 925-932-1031
Toll Free: 1-800-444-1821
FAX: 925-932-0560
Web. www.imagesales.com