

Specifications

Model Name	HiTi CS-310 & 320
Printing	Dye-Sub YMCKO Continuous Tone
Single/Double	Single Sided, Double sided printing
Resolution	300x300 dpi
Color Depth	256-level for each color / 16.77 million true colors
Gradations	YMCKO (Y:Yellow M: Magenta C:Cyan K: Black O:Overcoating)
Printer Operation	PC-Link
Printing Speed Mode:	35 sec/ YMCKO single side
Printing Quality Mode:	45 sec/ YMCKO single side
Printing Area	ISO CR-80 edge-to-edge (3.375 x 2.125 inch / 86 x 54 mm)
Acceptable Card Thickness	0.3 mm ~ 1.0 mm (10 mil ~ 40 mil)
Input Hopper Capacity	100 Cards (0.76 mm / 30 mil)
Message Display	LCD Control Panel
Power Requirement	100V~240V AC , 50/60Hz
Operating Temperature	15° ~ 32°C (59° ~ 90°F)
Operating Humidity	20 ~ 75% RH
Dimensions (WxHxD)	275 x 508 x 251 mm (10.8 x 20 x 9.9 inch)
Weight	8.6kg / 18.9 lbs
Standard Accessory	
PC Connection	AC power cord / USB cable / User manual / Driver CD / Software.
System Requirement	IBM-PC or compatible, Windows 2000/XP, PentiumR class 133MHz Computer with 128MB of RAM or higher, 100 MB free hard disk space or higher
Computer Interface	USB 1.1 & USB 2.0 Full Speed
Printer Driver	Windows 2000/XP
Bundled Software	Jolly Technologies, ID Flow
Optional Accessories	Magnetic Stripe Encoding Module ** Contactless Smart Card Encoding Module **
Consumables	YMCKO (200 prints ribbon + 200 cards) Resin K (1,000 prints)

** To install the optional modules, the original CS-300 card printer should be sent back to Hi-Touch Imaging Technologies for upgrade service.



Image Sales, Inc.
1559 Third Avenue
Walnut Creek, CA 94597
Phone: 925-932-1031
Toll Free: 1-800-444-1821
FAX: 925-932-0560
Web: www.imagesales.com



Warranty Upgrade provides a loaner printer with exact configuration by 2nd day shipping. 3 Year maximum renewal.
Service Agreement is 4 scheduled service calls per yr. to Clean, Calibrate & Adjust Printer within our local service area.